

# NKE 230/600-MB-W33 spherical roller bearings

NKE 230/600-MB-W33 spherical roller bearings Warehouse offers car parts Mounted Bearing Engineering Group and car accessories. We sell discount Metric Shaft Size Type online as well as cheap machinery parts.

|                         |                        |
|-------------------------|------------------------|
| Engineering Group       | Mounted Bearing        |
| Shaft Size              | 125 mm                 |
| Shaft Size Type         | Metric                 |
| Full Timken Part Number | QMPG26J125SB           |
| Locking Style           | Eccentric              |
| Weight                  | 134 lb                 |
| Housing Style           | Four-Bolt Pillow Block |
| UPC Code                | 0883450139588          |
| Dimension A             | 5.91 in                |
| Dimension B             | 11.08 in               |
| Dimension C             | 6.89 in                |
| Dimension D Max         | 17.63 in               |
| Dimension D Min         | 15.13 in               |
| Dimension E             | 3.15 in                |
| Dimension F             | 19.69 in               |
| Dimension G             | 5.040 in               |
| Dimension H             | 1.94 in                |
| Dimension J (Bolt Size) | 1.000 in               |
| Dimension K             | 2.31 in                |
| Dimension L             | 6.24 in                |
| Dimension M             | 3.72 in                |

|                                     |           |
|-------------------------------------|-----------|
| Dimension R                         | -0.27 in  |
| Dimension S                         | 6.040 in  |
| C0 – Static Load                    | 212000 lb |
| C – Dynamic Load (Basic)            | 170000 lb |
| e – Geometry Factor                 | 0.26      |
| Y1 – Geometry Factor                | 2.62      |
| Y2 – Geometry Factor                | 3.90      |
| Oil Lubrication – M/N Seal          | 700 rpm   |
| Oil Lubrication – T Seal            | 1500 rpm  |
| Oil Lubrication – B/C/O Seal        | 400 rpm   |
| Grease Lubrication – M/N Seal       | 700 rpm   |
| Grease Lubrication – T Seal         | 1000 rpm  |
| Grease Lubrication – B/C/O Seal     | 400 rpm   |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0050 in |
| Eng Internal Radial Clearance – Min | 0.0037    |
| Eng Internal Radial Clearance – Max | 0.0057    |
| Pre Install Clearance Min           | 0.0037 in |
| Pre Install Clearance Max           | 0.0057 in |