## NKE 32028-X tapered roller bearings

Online NKE 32028-X tapered roller bearings REXNORD Manufacturer Name Expert.More Choices. NKE 32028-X tapered roller bearings in Stock 0.0 Inventory & Ready to Ship Now!

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.22  |
| EAN                       | 0793699706383   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | UG243HL   |
| Seals                     | Floating Labyrinth  |
| Housing Configuration     | 1 Piece Solid   |
| Inch — Metric             | Inch  |
| Other Features            | Single Row   Standard Duty  <br>Standard Backing   Wide Inner<br>Race |

| Long Description              | 2 Bolt Pillow Block; 2-11/16"<br>Bore; 3" Base to Center Height;<br>Set Screw Mount; Ball Bearin |
|-------------------------------|--|
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P3U243JHK55  |
| Manufacturer Internal Number  | 0170638  |
| Weight / LBS                  | 15.9   |
| Actual Bolt Center to Center  | 8.1 Inch   206Millimeter   |
| D                             | 2.688 Inch   68.275 Millimeter   |
| Bolt Spacing Minimum          | 0 Inch   OMillimeter   |
| Nominal Bolt Center to Center | 8 Inch   203 Millimeter  |
| В                             | 3 Inch   76.2 Millimeter   |
| d                             | 2.688 Inch   68.275 Millimeter   |
| Bolt Spacing Maximum          | 0 Inch   OMillimeter   |