

NKE 52220 thrust ball bearings

NKE 52220 thrust ball bearings with easy-to-use parts 45x75x16 Size (mm) graphics, giving you the ability to check parts availability, pricing, examine remanufactured options. 45 Bore Diameter (mm)

Size (mm)	45x75x16
Bore Diameter (mm)	45
Outer Diameter (mm)	75
Width (mm)	16
d	45 mm
D	75 mm
B	16 mm
C	16 mm
a	2,49 mm
b	2,05 mm
f	1,65 mm
r min.	1 mm
r θ max.	0,6 mm
r l min.	0,5 mm
D1	71,83 mm
D2	81,6 mm
da min.	50 mm
Da max.	70 mm
Weight	0,245 Kg
Basic dynamic load rating (C)	21 kN
Basic static load rating (C θ)	15,1 kN

(Grease) Lubrication Speed	9200 r/min
(Oil) Lubrication Speed	11000 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.265
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	45MM Bore; 75MM Outside Diameter; 16MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove With Snap Ring
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.54013
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.953 Inch 75 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.772 Inch 45 Millimeter

Bearing No.	6009NR
r(min)	1
r1(min)	0.5
Cr	26.2
C0r	15.1
Cu	0.900
f0	15.3
Grease lub.	9200
Oil lub.	11000
D2(min)	81.6
f(ϕ)0.05)	1.65
da(min)	50
Da(max)	70
Dx(min)	83
Cy(max)	3.89
ra(max)	1
rb(max)	0.5
(Refer.) Mass (kg)	0.245