

# NKE 52232-MP thrust ball bearings

The online NKE 52232-MP thrust ball bearings parts store gives you immediate access to a selection of more 8 mm d than 1.4 million new, used, remanufactured.

d	8 mm
D	22 mm
B	7 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.01 kg
Dynamic load, C	3.35 kN
Static load, C <sub>0</sub>	1.4 kN
Fatigue limit load, C <sub>u</sub>	0.06 kN
f <sub>0</sub>	12.5
N <sub>lim</sub> (oil)	27,000 rpm
N <sub>lim</sub> (grease)	23,000 rpm
Min operating temperature, T <sub>min</sub>	-30 °C
Max operating temperature, T <sub>max</sub>	120 °C
da min	10 mm
da max	12.2 mm
Da max	20 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN

Minimum Buy Quantity	N/A
Weight / Kilogram	0.012
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	8MM Bore; 22MM Outside Diameter; 7MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1   ISO P0; No Fil
Other Features	Deep Groove   Low Torque Fluorinated Elastomer Rubber Friction Seal   -30 To 230 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.02645
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Bore	0.315 Inch   8 Millimeter

Outside Diameter	0.866 Inch   22 Millimeter
------------------	----------------------------