

NKE 54211+U211 thrust ball bearings

How do 10 mm B you find the NKE 54211+U211 thrust ball bearings specification? Manufacturers Online 75 mm d Free check

d	75 mm
D	95 mm
B	10 mm
rs min	0.6 mm
Radial clearance class	CN
Mass	0.14 kg
Dynamic load, C	12.5 kN
Static load, C ₀	12.9 kN
Fatigue limit load, C _u	0.59 kN
f ₀	16
N _{lim} (grease)	3,600 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	15.23 Hz
Characteristic outer ring frequency, BPF ₀	12.15 Hz
Characteristic inner ring frequency, BRF ₀	13.85 Hz
da min	79 mm
da max	80 mm

Da max	91 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Weight / LBS	0.317
Outside Diameter	3.74 Inch 95 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Bore	2.953 Inch 75 Millimeter
Inner Race Width	0 Inch 0 Millimeter