

NKE 6012-Z deep groove ball bearings

What is NKE 6012-Z deep groove ball bearings in 320 Outer Diameter (mm) mechanical engineering? Manufacturing Service . 150x320x72 Size (mm) Upload your CAD file 150 Bore Diameter (mm) for an instant.

| | |
|-------------------------------|------------|
| Size (mm) | 150x320x72 |
| Bore Diameter (mm) | 150 |
| Outer Diameter (mm) | 320 |
| Width (mm) | 72 |
| d | 150 mm |
| D | 320 mm |
| T | 72 mm |
| B | 65 mm |
| C | 55 mm |
| a | 60 mm |
| r min. | 5 mm |
| r1 min. | 4 mm |
| da min. | 177 mm |
| Da min | 276 mm |
| Da max. | 302 mm |
| db max. | 190 mm |
| Db min. | 292 mm |
| ra max. | 4 mm |
| rb max. | 3 mm |
| Weight | 25 Kg |
| Basic dynamic load rating (C) | 825 kN |

| | |
|-------------------------------|------------|
| Basic static load rating (C0) | 1060 kN |
| (Grease) Lubrication Speed | 1100 r/min |
| (Oil) Lubrication Speed | 1600 r/min |
| Calculation factor (e) | 0,35 |
| Calculation factor (Y0) | 0,96 |
| LangID | 1 |
| outer r | 4 |
| D_ | 320 |
| TC-BET22 | 0 |
| TC-BET21 | 4 |
| TC-BET23 | 0 |
| inner r | 5 |
| mass | 25 |
| GRS rpm | 1100 |
| D_b | 292 |
| Cr | 84500 |
| TC-RA | 645.435 |
| DE_ | 278.605 |
| T-ALP23 | 20 |
| db | 190 |
| T-ALP22 | 54 |
| Prod_Type3 | TRBSR_MD_A |
| da | 177 |
| T-ALP21 | 25 |
| Iso | 2GB |
| ALPHA_ | 12.953 |
| SDM_ | 236.057 |
| SBRG | 3 |
| D_a2 | 276 |

| | |
|----------|-------------|
| hidYobi | HR30330J |
| Y1 | 1.7 |
| D_a1 | 302 |
| B_ | 65 |
| hidTable | ecat_NSTPRM |
| Oil rpm | 1600 |
| C0r | 108000 |
| Y0 | 0.96 |
| TC-SLR | 47 |
| inner ra | 4 |
| outer rb | 3 |
| C0 | 1060 |
| Sa | 8 |
| Sb | 17 |
| e | 0.35 |
| DA_ | 43.422 |
| Z_ | 16 |
| C_ | 55 |
| yobi | HR30330J |
| TC-DA1 | 45.047 |
| TC-DA2 | 41.796 |
| KBRG | 3111 |
| DI_ | 193.508 |