## NKE 6201-Z-N deep groove ball bearings

NKE 6201-Z-N deep groove ball bearings Warehouse offers 10.4375 in overall length: car 8-1/8 in D parts and car accessories. We sell discount online as well as 2.9375 in d cheap machinery parts.

D8-1/8 inoverall length:10.4375 inbase width:3-3/16 inoverall height:6.4375 inexpansion type:Expansion Bearing (Floating)mounting:Two-Bolt Basefinish/coating:Uncoatedbearing type:Spherical Rollerseal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400		1
overall length:10.4375 inbase width:3-3/16 inoverall height:6.4375 inexpansion type:Expansion Bearing (Floating)mounting:Two-Bolt Basefinish/coating:Uncoatedbearing type:Spherical Rollerseal type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cast Ironseries:B22400	d	2.9375 in
base width: 3-3/16 in overall height: 6.4375 in expansion type: Expansion Bearing (Floating) mounting: Two-Bolt Base finish/coating: Uncoated bearing type: Spherical Roller seal type: Triple Lip bore type: Round radial dynamic load capacity: 51100 lbf housing construction: Split Pillow Block radial static load capacity: 71500 lbf base to bore centerline: 3.2500 in maximum rpm: 1150 RPM duty type: Heavy Duty lubrication type: Cannot Be Relubricated housing material: Cast Iron series: B22400	D	8-1/8 in
overall height:6.4375 inexpansion type:Expansion Bearing (Floating)mounting:Two-Bolt Basefinish/coating:Uncoatedbearing type:Spherical Rollerseal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	overall length:	10.4375 in
expansion type:Expansion Bearing (Floating)mounting:Two-Bolt Basefinish/coating:Uncoatedbearing type:Spherical Rollerseal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	base width:	3-3/16 in
mounting:Two-Bolt Basefinish/coating:Uncoatedbearing type:Spherical Rollerseal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	overall height:	6.4375 in
finish/coating:Uncoatedbearing type:Spherical Rollerseal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	expansion type:	Expansion Bearing (Floating)
bearing type:Spherical Rollerseal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	mounting:	Two-Bolt Base
seal type:Triple Lipbore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	finish/coating:	Uncoated
bore type:Roundradial dynamic load capacity:51100 lbfhousing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	bearing type:	Spherical Roller
radial dynamic load capacity: 51100 lbf housing construction: Split Pillow Block radial static load capacity: 71500 lbf base to bore centerline: 3.2500 in maximum rpm: 1150 RPM duty type: Heavy Duty lubrication type: Cannot Be Relubricated housing material: Cast Iron series: B22400	seal type:	Triple Lip
housing construction:Split Pillow Blockradial static load capacity:71500 lbfbase to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	bore type:	Round
radial static load capacity: 71500 lbf base to bore centerline: 3.2500 in maximum rpm: 1150 RPM duty type: Heavy Duty lubrication type: Cannot Be Relubricated housing material: Cast Iron series: B22400	radial dynamic load capacity:	51100 lbf
base to bore centerline:3.2500 inmaximum rpm:1150 RPMduty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	housing construction:	Split Pillow Block
maximum rpm: 1150 RPM duty type: Heavy Duty lubrication type: Cannot Be Relubricated housing material: Cast Iron series: B22400	radial static load capacity:	71500 lbf
duty type:Heavy Dutylubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	base to bore centerline:	3.2500 in
lubrication type:Cannot Be Relubricatedhousing material:Cast Ironseries:B22400	maximum rpm:	1150 RPM
housing material: Cast Iron series: B22400	duty type:	Heavy Duty
series: B22400	lubrication type:	Cannot Be Relubricated
	housing material:	Cast Iron
locking device: Set Screw	series:	B22400
	locking device:	Set Screw