

# NKE 6220-RSR deep groove ball bearings

170 Million used NKE 6220-RSR deep groove ball bearings instantly searchable. Shop 20x27x20 Size (mm) our large selection 20 Bore Diameter (mm) of parts based on brand, price, description, and location. Order the with stock ...

Size (mm)	20x27x20
Bore Diameter (mm)	20
Outer Diameter (mm)	27
Width (mm)	20
Fw	20 mm
D	27 mm
C	20 mm
Weight	0.027 Kg
Basic dynamic load rating (C)	17,7 kN
Basic static load rating (C0)	25,6 kN
(Grease) Lubrication Speed	8 000 r/min
Dw	2.5 mm
Lw	15.8 mm
Lubrication hole on outer ring	Non/No
Inner ring reference	IR17X20X20.5
Mass	0.03 kg
Cr	17.7 kN
C0r	25.6 kN
Nlim (grease)	8,000 rpm
Nlim (oil)	12,000 rpm
Min operating temperature, Tmin	-20 °C

Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.89 Hz
Characteristic outer ring frequency, BPF0	7.56 Hz
Characteristic inner ring frequency, BRFI	9.44 Hz
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.027
EAN	4547359073867
Product Group	B04144
bore diameter:	20 mm
static load capacity:	25600 N
outside diameter:	27 mm
bearing material:	Steel
overall width:	20 mm
cage material:	Steel
drawn cup type:	Open Ends
maximum rpm:	12000 rpm
closure type:	Open
precision rating:	ISO Class 0
number of rows:	One
series:	HMK
operating temperature range:	-40 to 250 °F, -40 to 120 °C
lubrication hole type:	No Hole
dynamic load capacity:	17700 N