## NKE N214-E-M6 cylindrical roller bearings

Shop NKE N214-E-M6 cylindrical roller bearings huge online discount inventory. 3-3/4 in Shaft Size and Import machinery parts your car needs with Free Shipping and Mounted Bearing Engineering Group Free Extended Warranty.

| Engineering Group        | Mounted Bearing         |
|--------------------------|-------------------------|
| Shaft Size               | 3-3/4 in                |
| Shaft Size Type          | Imperial                |
| Full Timken Part Number  | QVVFX22V312SB           |
| Locking Style            | Double V-Lock           |
| Weight                   | 55 lb                   |
| Housing Style            | Four-Bolt Square Flange |
| UPC Code                 | 0883450368117           |
| Dimension BC             | 11.75 in                |
| Dimension C              | 5.5 in                  |
| Dimension D              | 8.5000 in               |
| Dimension E              | 8.31 in                 |
| Dimension F              | 10.56 in                |
| Dimension H              | 1.50 in                 |
| Dimension J (Bolt Size)  | 1 in                    |
| Dimension L Exp          | 4.58 in                 |
| Dimension L Fix          | 4.49 in                 |
| Dimension N              | 3.960 in                |
| Dimension RVV            | 0.5 in                  |
| Dimension SVV            | 4.99 in                 |
| C — Dynamic Load (Basic) | 125000 lb               |

| CO — Static Load                    | 147000 lb |
|-------------------------------------|-----------|
| e — Geometry Factor                 | 0.26      |
| Y1 - Geometry Factor                | 2.55      |
| Y2 - Geometry Factor                | 3.80      |
| Oil Lubrication — M/N Seal          | 900 rpm   |
| Oil Lubrication — T Seal            | 1700 rpm  |
| Oil Lubrication — B/C/O Seal        | 600 rpm   |
| Grease Lubrication — M/N Seal       | 900 rpm   |
| Grease Lubrication — T Seal         | 1200 rpm  |
| Grease Lubrication — B/C/O Seal     | 600 rpm   |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0030 in |
| Eng Internal Radial Clearance — Min | 0.0053    |
| Eng Internal Radial Clearance — Max | 0.0067    |
| Pre Install Clearance Min           | 0.0043 in |
| Pre Install Clearance Max           | 0.0055 in |