

NKE NCF2980-V cylindrical roller bearings

NKE NCF2980-V cylindrical roller bearings 25 Bore Diameter (mm) Manufacturers , Online Wholesale Suppliers 25x47x12 Size (mm) !

| | |
|-------------------------------|---------------|
| Size (mm) | 25x47x12 |
| Bore Diameter (mm) | 25 |
| Outer Diameter (mm) | 47 |
| Width (mm) | 12 |
| d | 25 mm |
| D | 47 mm |
| B | 12 mm |
| C | 12 mm |
| r min. | 0,6 mm |
| da min. | 29 mm |
| da max | 30 mm |
| Da max. | 43 mm |
| ra max. | 0,6 mm |
| Weight | 0,079 Kg |
| Basic dynamic load rating (C) | 10,1 kN |
| Basic static load rating (C0) | 5,85 kN |
| (Grease) Lubrication Speed | 15 000 r/min |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.04 |
| EAN | 0029176012617 |

| | |
|---------------------------------|---|
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Non-Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 25MM Bore; 47MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | 6005VV |
| Weight / LBS | 0.08 |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Outside Diameter | 1.85 Inch 47 Millimeter |
| Bore | 0.984 Inch 25 Millimeter |
| SRI | 3.21 |
| hidYobi | 6005VV |
| LangID | 1 |
| D_ | 47 |
| SREX | 0.04 |
| B_ | 12 |

| | |
|------------|-------------|
| da min | 29 |
| hidTable | ecat_NSRDGB |
| SRE | 3.37 |
| mass | 0.079 |
| GRS rpm | 15000 |
| ra | 0.6 |
| SRIX | 0.02 |
| D_a | 43 |
| SRIN | 0 |
| C0 | 5.85 |
| fo | 14.5 |
| SREN | 0 |
| DE_ | 41.85 |
| Prod_Type3 | DGBB_SR_VV |
| DA_ | 6.35 |
| bomp | 0 |
| Z_ | 10 |
| yobi | 6005VV |
| C_conv | 10100 |
| ALPHA_ | 0 |
| SDM_ | 35.5 |
| r | 0.6 |
| KBRG | 6151 |
| SBRG | 10 |
| DI_ | 29.15 |