

# NKE NJ2216-E-MA6 cylindrical roller bearings

NKE NJ2216-E-MA6 cylindrical roller bearings 20 Bore Diameter (mm) SEARCH – Whether it's agriculture or construction equipment your working 20x35x24 Size (mm) on, Has the you need.

Size (mm)	20x35x24
Bore Diameter (mm)	20
Outer Diameter (mm)	35
Width (mm)	24
d	20 mm
A	35 mm
A1	24 mm
B	31 mm
H	66 mm
H1	33.3 mm
J	50.8 mm
L	73 mm
s1	18.3 mm
Basic dynamic load rating – C	12.7 kN
Basic static load rating – C0	6.6 kN
Fatigue load limit – Pu	0.28 kN
Limiting speed	5000 r/min
Calculation factor – f0	13
Weight	0.26 kg
Size thread – G	M8
Thread length – G1	12 mm

Hexagonal key size for grub screw – H	3 mm
Recommended tightening torque for grub screw	4 N·m
Housing	SYFWK 504 L
Bearing – YAR 204-2RF/VE495	YAR 2042RF/VE495
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	M06110
Housing material	Composite for food and beverage
A5	20.3 mm
Basic dynamic load rating C	12.7 kN
Basic static load rating C0	6.55 kN
Fatigue load limit Pu	0.28 kN
Mass bearing unit	0.26 kg
Thread size attachment end G	M8
Thread length G1	12 mm
Thread grub screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Bearing	YAR 204-2RF/VE495
End cover	ECL 204