

# NKE NJ2230-E-M6+HJ2230-E cylindrical roller bearings

High Quality NKE NJ2230-E-M6+HJ2230-E cylindrical roller bearings. Competitive Pricing. Accept 30x37x20 Size (mm) Small Order. Easy and Fast 37 Outer Diameter (mm) Shipping.

Size (mm)	30x37x20
Bore Diameter (mm)	30
Outer Diameter (mm)	37
Width (mm)	20
Fw	30 mm
D	37 mm
C	20 mm
Weight	0.040 Kg
Basic dynamic load rating (C)	22,3 kN
Basic static load rating (C0)	39,5 kN
(Grease) Lubrication Speed	5 500 r/min
Dw	2.5 mm
Lw	15.3 mm
Lubrication hole on outer ring	Non/No
Inner ring reference	IR25X30X20.5
Mass	0.04 kg
Cr	22.3 kN
C0r	39.5 kN
Nlim (grease)	5,500 rpm
Nlim (oil)	8,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	12.92 Hz
Characteristic outer ring frequency, BPF0	12 Hz
Characteristic inner ring frequency, BPI	14 Hz
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.04
EAN	4547359072273
Product Group	B04144
bore diameter:	30 mm
static load capacity:	39500 N
outside diameter:	37 mm
bearing material:	Steel
overall width:	20 mm
cage material:	Steel
drawn cup type:	Open Ends
maximum rpm:	8000 rpm
closure type:	Open
precision rating:	ISO Class 0
number of rows:	One
series:	HK
operating temperature range:	-40 to 250 °F, -40 to 120 °C
lubrication hole type:	No Hole
dynamic load capacity:	22300 N