

# NKE NJ2318-E-TVP3 cylindrical roller bearings

YOU'LL FIND AN EXTENSIVE SELECTION OF NKE NJ2318-E-TVP3 cylindrical roller bearings FOR 0.0 Inventory SALE.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 7.264   |
| EAN                       | 0883450104777   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | V Lock  |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22214   |
| Seals                     | Double Lip Nitrile Rubber   |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>60MM Bore; 165MM Bolt Circle;<br>117MM Bolt Spacing; 1 Piece<br>Solid; V Lo |

|                                       |                                |
|---------------------------------------|--------------------------------|
| Other Features                        | Double Row   Single Nut        |
| UNSPSC                                | 31171501                       |
| Harmonized Tariff Code                | 8483.20.40.80                  |
| Noun                                  | Bearing                        |
| Keyword String                        | Flanged                        |
| Weight / LBS                          | 16                             |
| Cartridge Pilot Diameter              | 5.512 Inch   140 Millimeter    |
| Cartridge Pilot Depth                 | 1.125 Inch   28.575 Millimeter |
| Nominal Bolt Circle Diameter<br>Round | 6.5 Inch   165 Millimeter      |
| d                                     | 2.362 Inch   60 Millimeter     |
| Bolt Spacing                          | 4.6 Inch   117 Millimeter      |
| D                                     | 3.19 Inch   81.026 Millimeter  |