NKE NJ2338-E-M6 cylindrical roller bearings

With over 10170 full-service stores, Mounted Bearing Engineering Group our NKE NJ2338-E-M6 cylindrical roller bearings inventory is extensive and our parts are priced right. within 2-7/16 in Shaft Size 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

| Engineering Group | Mounted Bearing |
|-------------------------|------------------------|
| Shaft Size | 2-7/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | TAPH15K207SB |
| Locking Style | Tapered Adapter |
| Weight | 29 lb |
| Housing Style | Four-Bolt Pillow Block |
| UPC Code | 0883450129077 |
| Dimension A | 3.25 in |
| Dimension B | 6.38 in |
| Dimension C | 3.86 in |
| Dimension D Max | 9.69 in |
| Dimension D Min | 7.94 in |
| Dimension E | 1.88 in |
| Dimension F | 10.88 in |
| Dimension G | 3.130 in |
| Dimension H | 1.29 in |
| Dimension J (Bolt Size) | 0.500 in |
| Dimension L | 3.29 in |
| Dimension M | 1.73 in |

| Dimension S | 2.87 in |
|---------------------------------------|-----------|
| C0 — Static Load | 54100 lb |
| C — Dynamic Load (Basic) | 49900 lb |
| e – Geometry Factor | 0.22 |
| Y1 – Geometry Factor | 3.14 |
| Y2 – Geometry Factor | 4.67 |
| Oil Lubrication — M/N Seal | 1600 rpm |
| Oil Lubrication – T Seal | 2900 rpm |
| Oil Lubrication — B/C/O Seal | 1300 rpm |
| Grease Lubrication — M/N Seal | 1600 rpm |
| Grease Lubrication — T Seal | 2400 rpm |
| Grease Lubrication — B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0035 in |
| Pre Install Clearance Min | 0.0037 in |
| Pre Install Clearance Max | 0.0047 in |
| Int Radial Clearance Reduction Min | 0.0015 in |
| Int Radial Clearance Reduction Max | 0.0020 in |
| Adapter Sleeve Axial Movement Min | 0.022 in |
| Adapter Sleeve Axial Movement Max | 0.03 in |
| Post Install Int Radial Clearance Min | 0.0017 in |