

# NKE NU1022-E-M6 cylindrical roller bearings

NKE NU1022-E-M6 cylindrical roller bearings Deal is 0.0 Inventory your source for OEM and accessories. We sell Genuine at discount prices.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 16.71   |
| EAN                       | 0808250334902   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Adapter Sleeve  |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 20 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | UKX20   |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Round Flange Cartridge; 3-7/16" Bore; 9.3" Bolt Circle; 6.6" Bolt Spacing; 1 P |

|                                    |                                      |
|------------------------------------|--------------------------------------|
| Other Features                     | Single Row   Spherical   Medium Duty |
| UNSPSC                             | 31171501                             |
| Harmonized Tariff Code             | 8483.20.40.40                        |
| Noun                               | Bearing                              |
| Keyword String                     | Flanged                              |
| Weight / LBS                       | 36.8                                 |
| Cartridge Pilot Diameter           | 8.125 Inch   206.375 Millimeter      |
| Nominal Bolt Circle Diameter Round | 9.3 Inch   236.2 Millimeter          |
| Cartridge Pilot Depth              | 1.102 Inch   28 Millimeter           |
| D                                  | 3.819 Inch   97 Millimeter           |
| Bolt Spacing                       | 6.6 Inch   167.6 Millimeter          |
| d                                  | 3.438 Inch   87.325 Millimeter       |