

NKE NU228-E-MPA cylindrical roller bearings

LET OUR NKE NU228-E-MPA cylindrical roller bearings EXPERTS 20 mm d GET YOU THE PARTS YOU NEED.

| | |
|---|------------|
| d | 20 mm |
| D | 52 mm |
| B | 18 mm |
| B1 | 29 mm |
| d3 | 38 mm |
| D2 ≈ | 46.21 mm |
| B2 | 10.5 mm |
| r1,2 min. | 1 mm |
| da max. | 31 mm |
| db min. | 28 mm |
| Da max. | 46.4 mm |
| Ba min. | 5 mm |
| ra max. | 1 mm |
| Basic dynamic load rating C | 14.3 kN |
| Basic static load rating C0 | 4 kN |
| Fatigue load limit Pu | 0.21 kN |
| Limiting speed | 9000 r/min |
| Permissible angular misalignment α | 1.5 ° |
| Calculation factor kr | 0.045 |
| Calculation factor e | 0.28 |
| Calculation factor Y0 | 2.5 |
| Calculation factor Y1 | 2.2 |
| Calculation factor Y2 | 3.5 |

| |
|-------------------------------|
| Mass bearing + adapter sleeve |
|-------------------------------|

| |
|---------|
| 0.23 kg |
|---------|