

# NKE NUP2318-E-M6 cylindrical roller bearings

offers a N/A Minimum Buy Quantity NKE NUP2318-E-M6 cylindrical roller bearings selection of Genuine 0.0 Inventory at Wholesale Prices. We are a NKE NUP2318-E-M6 cylindrical roller bearings Certified Parts Retailer

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.607   |
| EAN                       | 0808250297269   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 3   |
| Mounting Method           | Set Screw   |
| Housing Style             | 3 Bolt Flange Bracket   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Nickel Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 7/16 Inch   |
| Relubricatable            | Yes   |
| Insert Part Number        | MUC207-21   |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 3 Bolt Flange Bracket; 1-5/16" Bore; 1-1/4" Bolt Spacing; 1 Piece Solid; Set Screw Mount; |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Normal Duty   Has Slinger |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40                                      |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | MUCFB207-21NP                                      |
| Weight / LBS                       | 2.9  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter                              |
| Nominal Bolt Circle Diameter Round | 0 Inch   0 Millimeter                              |
| d                                  | 1.313 Inch   33.35 Millimeter                      |
| Bolt Spacing                       | 1.25 Inch   31.75 Millimeter                       |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter                              |
| D                                  | 1.689 Inch   42.9 Millimeter                       |