

NKE NUP312-E-M6 cylindrical roller bearings

NKE NUP312-E-M6 cylindrical roller bearings with easy-to-use parts 80,000 Bore Diameter (mm) graphics, giving you the ability 80x170x68.300 Size (mm) to 170,000 Outer Diameter (mm) check parts availability, pricing, examine remanufactured options.

Size (mm)	80x170x68.300
Bore Diameter (mm)	80,000
Outer Diameter (mm)	170,000
Width (mm)	68,300
d	80,000 mm
D	170,000 mm
B	68,300 mm
C	68,300 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359664638
Product Group	B00234
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No

Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 170MM Outside Diameter; 68.28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	63316LLU
Weight / LBS	13.603
Bore	3.15 Inch 80 Millimeter
Outer Race Width	2.688 Inch 68.28 Millimeter
Outside Diameter	6.693 Inch 170 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	80 mm
precision rating:	ISO Class 0
outside diameter:	170 mm
finish/coating:	Uncoated
overall width:	68.3 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel

closure type:	Double Sealed
inner ring width:	68.30 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	68.30 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	2700 rpm
internal clearance:	CN
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 °C
series:	633
dynamic load capacity:	123000 N
manufacturer product page:	Click here
static load capacity:	86500 N