

NKX10T2Z NTN r min. 0.3 mm 10x25x23mm Complex bearings

| | |
|---------------------------------|-----------|
| dw | 10 mm |
| rs min | 0.3 mm |
| Dw | 1.5 mm |
| Dw1 | 4.76 mm |
| Lw | 7.8 mm |
| Lubrication hole on outer ring | Oui/Yes |
| Precision class | P0 |
| Mass | 0.04 kg |
| Cr | 5.45 kN |
| Ca | 10 kN |
| C0r | 6.45 kN |
| C0a | 14 kN |
| Nlim (grease) | 6.700 rpm |
| Nlim (oil) | 9.500 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| da min | 18 mm |
| ras max | 0.3 mm |
| Bearing number | NKX10T2Z |
| Size (mm) | 10x25x23 |
| Brand | NTN |
| Bore Diameter (mm) | 10 |
| Outer Diameter (mm) | 25 |
| Width (mm) | 23 |
| d | 10 mm |

| | |
|--------------------------------|------------|
| Fw | 10 mm |
| D | 19 mm |
| D1 | 24 mm |
| D2 | 25 mm |
| C | 23 mm |
| a | 19.7 mm |
| r min. | 0.3 mm |
| C1 | 9 mm |
| da min. | 18 mm |
| ra max. | 0.3 mm |
| C2 | 6.5 mm |
| Weight | 0.039 Kg |
| Dynamic load rating radial (C) | 5.45 kN |
| Dynamic load rating axial (C) | 10 kN |
| Static load rating radial (C0) | 6.45 kN |
| Static load rating axial (C0) | 14 kN |
| (Grease) Lubrication Speed | 6700 r/min |
| Category | Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.044 |
| Product Group – BDI | B04144 |