

NMB R-1640HH deep groove ball bearings

Find the discount 25 Bore Diameter (mm) NMB R-1640HH deep groove ball bearings online 120 Outer Diameter (mm) you need . We offer ... If you check out our large selection of NMB R-1640HH deep groove ball bearings 25x120x82 Size (mm) once .

| | |
|------------------------------------|-------------|
| Size (mm) | 25x120x82 |
| Bore Diameter (mm) | 25 |
| Outer Diameter (mm) | 120 |
| Width (mm) | 82 |
| d | 25 mm |
| H | 120 mm |
| A | 82 mm |
| A1 | 78.74 mm |
| A2 | 32 mm |
| A3 | 15 mm |
| d1 | 34 mm |
| D1 | 88 mm |
| D2 | 80 mm |
| D3 | 40 mm |
| Basic dynamic load rating – C | 36.5 kN |
| Basic static load rating – C0 | 104 kN |
| Fatigue load limit – Pu | 3.9 kN |
| Limiting speed, Preload class A | 4500 r/min |
| Limiting speed for oil lubrication | 2250 mm/min |
| Preload class A | 3160 N |
| Preload class B | 6320 N |

| | |
|--|---------------|
| Frictional moment, Preload class A | 0.138 N·m |
| Frictional moment, Preload class B | 0.24 N·m |
| Static Axial rigidity, Preload class A | 1450 N/micron |
| Static Axial rigidity, Preload class B | 1850 N/micron |
| Basic dynamic load rating C | 36.5 kN |
| Basic static load rating C0 | 104 kN |
| Fatigue load limit Pu | 3.86 kN |
| Attainable speed for preload class A | 4500 r/min |
| Attainable speed for preload class B | 2250 r/min |
| Frictional moment for preload class A | 0.138 N·m |
| Frictional moment for preload class B | 0.24 N·m |
| Static axial stiffnes for preload class A | 1450 N/μm |
| Static axial stiffnes for preload class B | 1850 N/μm |
| Mass cartridge unit | 3.5 kg |
| Through hole diameter for attachment bolts N | 9.2 mm |
| Pitch diameter of attachment bolt holes J | 102 mm |
| Cartridge half diameter without flange J1 | 44 mm |