

# NMB R-3 deep groove ball bearings

What is NMB R-3 deep groove ball bearings in mechanical engineering? N/A Minimum Buy Quantity Manufacturing 0.0 Inventory Service . Upload your CAD file for an instant.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 8.626   |
| EAN                       | 0883450228220   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | V Lock  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22214   |
| Seals                     | Triple Lip Urethane   |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Metric  |
| Other Features            | Double Row   Double Nut   |
| Long Description          | 2 Bolt Pillow Block; 60MM Bore; 70MM Base to Center Height; V Lock Mount; Spherical Roller Bearing; |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QVVPL14V060SE0                 |
| Weight / LBS                  | 22                             |
| Nominal Bolt Center to Center | 7.1 Inch   181 Millimeter      |
| Bolt Spacing Maximum          | 7.44 Inch   188.976Millimeter  |
| B                             | 2.756 Inch   70 Millimeter     |
| D                             | 4.09 Inch   103.886 Millimeter |
| Bolt Spacing Minimum          | 6.81 Inch   172.974Millimeter  |
| d                             | 2.362 Inch   60 Millimeter     |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |