

NSK 1204 K self aligning ball bearings

Various 50x90x20 Size (mm) 50 Bore Diameter (mm) types and sizes to accommodate your NSK 1204 K self aligning ball bearings requirements.

| | |
|-------------------------------|------------|
| Size (mm) | 50x90x20 |
| Bore Diameter (mm) | 50 |
| Outer Diameter (mm) | 90 |
| Width (mm) | 20 |
| d | 50 mm |
| Fw | 59,5 mm |
| D | 90 mm |
| B | 20 mm |
| C | 20 mm |
| r min. | 1,1 mm |
| r1 min. | 1,1 mm |
| da min. | 56,5 mm |
| Da max. | 83,5 mm |
| db max. | 57 mm |
| db min | 56,5 mm |
| ra max. | 1 mm |
| rb max. | 1 mm |
| S | 1,7 mm |
| Basic dynamic load rating (C) | 69 kN |
| Basic static load rating (C0) | 76,5 kN |
| (Grease) Lubrication Speed | 7100 r/min |
| Inventory | 0.0 |

| | |
|----------------------|---------------|
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.475 |
| EAN | 0029176867002 |
| Product Group | B04144 |
| hidYobi | NU210EM |
| LangID | 1 |
| D_ | 90 |
| Macha rpm | 9000 |
| B_ | 20 |
| hidTable | ecat_NSCLDR |
| Oil rpm | 7500 |
| rb | 1 |
| mass | 0.551 |
| GRS rpm | 6300 |
| ra | 1 |
| db max | 57 |
| TSR rpm | 8000 |
| C0 | 76.5 |
| DE_ | 81.5 |
| Prod_Type3 | CRB_SR_NU |
| da | 56.5 |
| DA_ | 11 |
| Z_ | 17 |
| D_a max | 83.5 |
| yobi | NU210EM |
| dd min | 67 |
| C_conv | 69000 |
| ALPHA_ | 0 |

| | |
|--------|------|
| SDM_ | 70.5 |
| r | 1.1 |
| dc min | 62 |
| KBRG | 4145 |
| SBRG | 2 |
| r1 | 1.1 |
| DI_ | 59.5 |