

# NSK 130RNP2107 cylindrical roller bearings

Shop 0.0 Inventory NSK 130RNP2107 cylindrical roller bearings huge online discount inventory. and Import machinery parts your car needs with Free Shipping and Free Extended Warranty.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.67  |
| EAN                       | 0808250150274   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Flange Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Thermoplastic   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | UC207-22MZ2   |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 2 Bolt Flange Block; 1-3/8" Bore; 5.1" Bolt Circle; 5-1/8" Bolt Spacing; 1 Piece Soli |

|                                    |   |
|------------------------------------|---|
| Other Features                     | Single Row   Spherical   Normal Duty   Zinc Coated Insert   White Housing   Has Slinger |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.40   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Manufacturer Item Number           | UCNFL207-22MZ2W   |
| Weight / LBS                       | 1.47  |
| D                                  | 1.689 Inch   42.9 Millimeter  |
| Nominal Bolt Circle Diameter Round | 5.1 Inch   130 Millimeter   |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter   |
| d                                  | 1.375 Inch   34.925 Millimeter  |
| Bolt Spacing                       | 5.125 Inch   130.18 Millimeter  |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter   |