

NSK 160KBE43+L tapered roller bearings

Manufacturers of all 62x30x16 Size (mm) are represented in our partial list of clients. 62 Bore Diameter (mm) Contact Gary for a complete NSK 160KBE43+L tapered roller bearings list of clients and projects.

| | |
|-------------------------------|-------------|
| Size (mm) | 62x30x16 |
| Bore Diameter (mm) | 62 |
| Outer Diameter (mm) | 30 |
| Width (mm) | 16 |
| d | 30 mm |
| D | 62 mm |
| B | 16 mm |
| d1 | 39.5 mm |
| D1 | 52.9 mm |
| r1,2 – min. | 1 mm |
| da – min. | 35.6 mm |
| Da – max. | 56.4 mm |
| ra – max. | 1 mm |
| Basic dynamic load rating – C | 23.4 kN |
| Basic static load rating – C0 | 12.9 kN |
| Fatigue load limit – Pu | 0.54 kN |
| Reference speed | 24000 r/min |
| Limiting speed | 15000 r/min |
| Calculation factor – kr | 0.025 |
| Calculation factor – f0 | 13 |
| Inventory | 0.0 |

| | |
|---------------------------------|--|
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.19 |
| EAN | 7316571401416 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Polyamide |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil |
| Other Features | Deep Groove Reinforced Ball Set |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | 6206 ETN9 |
| Weight / LBS | 0.439 |
| Outer Race Width | 0.63 Inch 16 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 1.181 Inch 30 Millimeter |
| Outside Diameter | 2.441 Inch 62 Millimeter |

| | |
|------------------------------|----------------------------|
| bore diameter: | 30 mm |
| static load capacity: | 12.9 kN |
| outside diameter: | 62 mm |
| finish/coating: | Uncoated |
| overall width: | 16 mm |
| bearing material: | Steel |
| bore type: | Round |
| cage material: | Polyamide 66 |
| closure type: | Open |
| fillet radius: | 1 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| maximum rpm: | 24000 rpm |
| snap ring included: | Without Snap Ring |
| weight: | 0.4 lb |
| operating temperature range: | -40 to 212 °F °F |
| manufacturer product page: | Click here |
| dynamic load capacity: | 23.4 kN |
| manufacturer upc number: | 7316571401416 |
| d1 ≈ | 39.5 mm |
| D1 ≈ | 52.9 mm |
| r1,2 min. | 1 mm |
| da min. | 35.6 mm |
| Da max. | 56.4 mm |
| ra max. | 1 mm |
| Basic dynamic load rating C | 23.4 kN |
| Basic static load rating C0 | 12.9 kN |
| Fatigue load limit Pu | 0.54 kN |
| Calculation factor kr | 0.025 |
| Calculation factor f0 | 13 |

| | |
|--------------|---------|
| Mass bearing | 0.18 kg |
|--------------|---------|