

NSK 32BWK09-Y-2CP17-01 E tapered roller bearings

100% Authentic. 70x150x35 Size (mm) 70 Bore Diameter (mm) NSK 32BWK09-Y-2CP17-01 E tapered roller bearings Highest Quality. Certified Supplier.

| | |
|-------------------------------|-------------|
| Size (mm) | 70x150x35 |
| Bore Diameter (mm) | 70 |
| Outer Diameter (mm) | 150 |
| Width (mm) | 35 |
| d | 70 mm |
| D | 150 mm |
| B | 35 mm |
| C | 35 mm |
| ra1 max. | 1 mm |
| Angle (α) | 40 ° |
| a | 63,5 mm |
| r min. | 2,1 mm |
| r1 min. | 1,1 mm |
| 2B | 70 mm |
| da min. | 82 mm |
| ra max. | 2 mm |
| Db max | 143 mm |
| Weight | 5,22 Kg |
| Basic dynamic load rating (C) | 186 kN |
| Basic static load rating (C0) | 172 kN |
| (Grease) Lubrication Speed | 3 500 r/min |
| Inventory | 0.0 |

| | |
|---------------------------------|--|
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 5.22 |
| EAN | 4547359451948 |
| Product Group | B00308 |
| Enclosure | Open |
| Flush Ground | Yes |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Single Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 40 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 2 (1 Pair) |
| Mounting Arrangement | Duplex-Back to Back |
| Inch – Metric | Metric |
| Long Description | 70MM Bore; 150MM Outside Diameter; 70MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of B |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Outside Diameter | 5.906 Inch 150 Millimeter |
| Bore | 2.756 Inch 70 Millimeter |
| Width | 2.756 Inch 70 Millimeter |