## NSK 42381/42584 tapered roller bearings

Advance NSK 42381/42584 tapered roller bearings is your source for quality 0.0 Inventory and accessories. shop online N/A Minimum Buy Quantity for home delivery or pick up ABB MOTORS AND MECHANICAL INC Manufacturer Name in one of our 10000.

| Inventory                 | 0.0                           |
|---------------------------|-------------------------------|
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC |
| Minimum Buy Quantity      | N/A                           |
| Weight                    | 35.38                         |
| EAN                       | 0782475035762                 |
| Product Group             | M06288                        |
| Number of Mounting Holes  | 2                             |
| Mounting Method           | Tapered Adapter Sleeve        |
| Housing Style             | 2 Bolt Pillow Block           |
| Rolling Element           | Tapered Roller Bearing        |
| Housing Material          | Cast Iron                     |
| Expansion / Non-expansion | Non-expansion                 |
| Mounting Bolts            | 3/4 Inch                      |
| Relubricatable            | Yes                           |
| Insert Part Number        | DU-SD-210                     |
| Seals                     | Dual Piston Ring Seal         |
| Housing Configuration     | 2 Piece Split                 |
| Inch — Metric             | Inch                          |
| Other Features            | Double Row   Special Duty     |

| Long Description                 | 2 Bolt Pillow Block; 2-5/8"<br>Bore; 4-3/4" Base to Center<br>Height; Tapered Adapter Sleeve<br>Mou |
|----------------------------------|---|
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.80   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Manufacturer Item Number         | P2B-SD-210 SPECIAL DUTY   |
| Manufacturer Internal Number     | 066223  |
| Weight / LBS                     | 84  |
| Bolt Spacing Minimum             | 11 Inch   279.4Millimeter   |
| D                                | 5.75 Inch   146.05 Millimeter   |
| d                                | 2.625 Inch   66.675 Millimeter  |
| Bolt Spacing Maximum             | 12.5 Inch   317.5Millimeter   |
| В                                | 4.75 Inch   120.65 Millimeter   |
| Nominal Bolt Center to<br>Center | 11.8 Inch   300 Millimeter  |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter  |