

NSK 54416 thrust ball bearings

NSK 54416 thrust ball bearings Engineering Calculator 50x85x26 Size (mm) , Manufacturing Service . Get Your Free. 85 Outer Diameter (mm)

Size (mm)	50x85x26
Bore Diameter (mm)	50
Outer Diameter (mm)	85
Width (mm)	26
d	50 mm
D	85 mm
T	26 mm
B	26 mm
C	20 mm
a	20,3 mm
r min.	1,5 mm
r1 min.	1,5 mm
da min.	61 mm
Da min	74 mm
Da max.	76 mm
db max.	56 mm
Db min.	82 mm
ra max.	1,5 mm
rb max.	1,5 mm
Weight	0,597 Kg
Basic dynamic load rating (C)	89 kN
Basic static load rating (C0)	126 kN

(Grease) Lubrication Speed	4300 r/min
(Oil) Lubrication Speed	5600 r/min
Calculation factor (e)	0,41
Calculation factor (Y0)	0,8
LangID	1
outer r	1.5
D_	85
TC-BET22	26
TC-BET21	3
TC-BET23	0
inner r	1.5
mass	0.597
GRS rpm	4300
D_b	82
Cr	9100
TC-RA	152.569
DE_	75.698
T-ALP23	0
db	56
T-ALP22	40
Prod_Type3	TRBSR_MD_A
da	61
T-ALP21	30
Iso	3CE
ALPHA_	15.333
SDM_	67.324
SBRG	31
D_a2	74
hidYobi	HR33110J

Y1	1.5
D_a1	76
B_	26
hidTable	ecat_NSTPRM
Oil rpm	5600
C0r	12800
Y0	0.8
TC-SLR	19
inner ra	1.5
outer rb	1.5
C0	126
Sa	4
Sb	6
e	0.41
DA_	8.574
Z_	22
C_	20
yobi	HR33110J
TC-DA1	9.141
TC-DA2	8.006
KBRG	3111
DI_	58.95