

# NSK 6206L11-H-20DDU deep groove ball bearings

We Provide Extensive NSK 6206L11-H-20DDU deep groove ball bearings Selection And Competitive Wholesale 254 mm da Pricing.

da	254 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	379.413 mm
ba	100.806 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J1	139.7 mm
L	869.95 mm
N1	41.275 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	73.025 mm
Housing	SAFS 056 KAUB
Bearing	23056 CCK/W33
Adapter sleeve assembly	SNP 3056×10

Stabilizing ring	2 x A8819
Taconite seal	TER 568
End plug (suffix Y)	X-5217-2
Max. speed for Taconite seal	310 r/min
P60°	669 kN
P90°	400 kN
P120°	249 kN
P150°	222 kN
P180°	267 kN
Pa	89 kN
Mass pillow block	324 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g