

NSK 6222DDU deep groove ball bearings

Offer 25 Outer Diameter (mm) High Quality Brand NSK 6222DDU deep groove ball bearings .Contact Us Online to Get 20x25x38 Size (mm) Best Quote.

Size (mm)	20x25x38
Bore Diameter (mm)	20
Outer Diameter (mm)	25
Width (mm)	38
d	25 mm
A	38 mm
A1	24 mm
B1	35 mm
H	21.5 mm
H1	36.5 mm
H2	16 mm
J	102.5 mm
J – max.	111 mm
J – min.	94 mm
L	140 mm
N1	13 mm
s1	20.5 mm
J6	130 mm
J7	14 mm
N4	4 mm
DN	6.5 mm
SWN	7 mm

GN – 1/4-28 SAE-LT	1/428 SAELT
RG – 1/4-28 UNF	1/428 UNF
R1	2 mm
Rα	45 °
Basic dynamic load rating – C	14 kN
Basic static load rating – C0	7.8 kN
Fatigue load limit – Pu	0.335 kN
Limiting speed	7000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.759
EAN	7316570141917
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Adapter Sleeve
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes
Insert Part Number	YSA 205-2FK
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row Y Bearing

Long Description	2 Bolt Pillow Block; 20MM Bore; 36.5MM Base to Center Height; Adapter Sleeve Mount; Ball Bearing; Re
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SYJ 25 KF
Weight / LBS	1.39
Bore	0.787 Inch 20 Millimeter
Actual Bolt Center to Center	4 Inch 102Millimeter
Nominal Bolt Center to Center	4.1 Inch 105 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Base to Center Height	1.437 Inch 36.5 Millimeter
Length Thru Bore	1.378 Inch 35 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Housing material	Cast iron
J max.	111 mm
J min.	94 mm
N	21.5 mm
RG	1/4-28 UNF
Rα	45 °
GN	1/4-28 SAE-LT
Basic dynamic load rating C	14 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Mass bearing unit	0.89 kg
Appropriate spanner	HN 5-6

Recommended lock nut tightening angle α	90 °
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	SYJ 505
Bearing	YSA 205-2FK
Adapter sleeve	H 2305