

# NSK 65BNR20HV1V angular contact ball bearings

How do you find the NSK 65BNR20HV1V angular contact ball bearings 42 Bore Diameter (mm) specification? Manufacturers 42x20x12 Size (mm) Online Free 20 Outer Diameter (mm) check

Size (mm)	42x20x12
Bore Diameter (mm)	42
Outer Diameter (mm)	20
Width (mm)	12
d	20 mm
D	42 mm
B	12 mm
d2	24.65 mm
D2	37.19 mm
r1,2 – min.	0.6 mm
da – min.	23.2 mm
da – max.	24.5 mm
Da – max.	38.8 mm
ra – max.	0.6 mm
Basic dynamic load rating – C	10 kN
Basic static load rating – C0	5 kN
Fatigue load limit – Pu	0.212 kN
Reference speed	38000 r/min
Limiting speed	19000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	14
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.075
EAN	7316571823829
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 42MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Low Friction   NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6004-2RSL
Weight / LBS	0.158
Inner Race Width	0 Inch   0 Millimeter
Bore	0.787 Inch   20 Millimeter
Outer Race Width	0.472 Inch   12 Millimeter

Outside Diameter	1.654 Inch   42 Millimeter
d2 ≈	24.65 mm
D2 ≈	37.19 mm
r1,2 min.	0.6 mm
da min.	23.2 mm
da max.	24.5 mm
Da max.	38.8 mm
ra max.	0.6 mm
Basic dynamic load rating C	9.95 kN
Basic static load rating C0	5 kN
Fatigue load limit Pu	0.212 kN
Calculation factor kr	0.025
Calculation factor f0	14
Mass bearing	0.069 kg