

# NSK 99550/99098X cylindrical roller bearings

Advance NSK 99550/99098X cylindrical roller bearings is your source for quality and accessories. shop online for home delivery or pick N/A Minimum Buy Quantity up in one of 0.0 Inventory our 10000 .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 11.804   |
| EAN                       | 0883450353571  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                                      |
| Housing Style             | 2 Bolt Pillow Block                                    |
| Rolling Element           | Spherical Roller Bearing                               |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 16 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22213  |
| Seals                     | Double Lip Viton                                       |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Single Collar   SN Style   With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 65MM Bore; 80MM Base to Center Height; Concentric Collar Mount; Spherical Rolle |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QASN13A065SC   |
| Weight / LBS                  | 35   |
| D                             | 3.386 Inch   86 Millimeter   |
| Bolt Spacing Minimum          | 7.717 Inch   196Millimeter   |
| Bolt Spacing Maximum          | 9.252 Inch   235Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Nominal Bolt Center to Center | 8.5 Inch   215.5 Millimeter  |
| d                             | 2.559 Inch   65 Millimeter   |
| B                             | 3.15 Inch   80 Millimeter  |