

# NSK B15-94DG3 deep groove ball bearings

NSK B15-94DG3 deep groove ball bearings with easy-to-use parts graphics, giving you the ability to check parts availability, pricing, 0.0 Inventory examine remanufactured options.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ASAHI BEARINGS                                     |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 31.51  |
| EAN                       | 0808250276868                                      |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Adapter Sleeve                                     |
| Housing Style             | 2 Bolt Pillow Block                                |
| Rolling Element           | Ball Bearing                                       |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion                                      |
| Mounting Bolts            | 27 Millimeter                                      |
| Relubricatable            | Yes  |
| Insert Part Number        | UKX20+H2320  |
| Seals                     | Contact Seal                                       |
| Housing Configuration     | 1 Piece Solid                                      |
| Inch – Metric             | Metric   |
| Other Features            | Single Row   Spherical   Medium Duty   Has Slinger |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 90MM Bore; 127MM Base to Center Height; Adapter Sleeve Mount; Ball Bearing; 299 |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | UKPX20+H2320   |
| Weight / LBS                  | 69.4   |
| Nominal Bolt Center to Center | 13.3 Inch   336.8 Millimeter   |
| Bolt Spacing Minimum          | 11.772 Inch   299Millimeter  |
| d                             | 3.543 Inch   90 Millimeter   |
| B                             | 5 Inch   127 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Maximum          | 14.764 Inch   375Millimeter  |
| D                             | 3.819 Inch   97 Millimeter   |