

# NSK F626DD deep groove ball bearings

NSK F626DD deep groove ball bearings 30 Outer Diameter (mm) manufacturer 78x30x49 Size (mm) and global supplier of reliable ball and roller ... NSK F626DD deep groove ball bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our targeted industries.

Size (mm)	78x30x49
Bore Diameter (mm)	78
Outer Diameter (mm)	30
Width (mm)	49
d	30 mm
D	78 mm
H	49 mm
D1	40 mm
B	12 mm
r1,2 – min.	1 mm
r3,4 – min.	0.6 mm
da	40 mm
Da – max.	55 mm
ra – max.	1 mm
rb – max.	0.6 mm
Basic dynamic load rating – C	61.8 kN
Basic static load rating – C0	122 kN
Fatigue load limit – Pu	4.5 kN
Reference speed	2200 r/min
Limiting speed	3000 r/min

Minimum load factor – A	0.077
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.036
EAN	7316577121301
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1   ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row
Long Description	30MM Bore 1; 42MM Bore 2; 78MM Outside Diameter; 49MM Height; Ball Bearing; Double Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	52308
Weight / LBS	2.281
Outside Diameter	3.071 Inch   78 Millimeter
Bore 2	1.654 Inch   42 Millimeter
Bore 1	1.181 Inch   30 Millimeter

Overall Height with Aligning Washer	0 Inch   0 Millimeter
Height	1.929 Inch   49 Millimeter
bore diameter:	30 mm
static load capacity:	122 kN
outside diameter:	78 mm
dynamic load capacity:	61.8 kN
overall width:	49 mm
maximum rpm:	3000 RPM
thrust bearing type:	Double-Direction
cage material:	Steel
outside diameter design:	Straight
fillet radius:	0.6 mm
separable or banded:	Separable
series:	523
precision rating:	ABEC 1 (ISO Class Normal)
D1 ≈	40 mm
r1,2 min.	1 mm
r3,4 min.	0.6 mm
Da max.	55 mm
ra max.	1 mm
rb max.	0.6 mm
Basic dynamic load rating C	61.8 kN
Basic static load rating C0	122 kN
Fatigue load limit Pu	4.5 kN
Minimum load factor A	0.077
Mass bearing (including seat washer where applicable)	1.05 kg