

# NSK FWJ-182417 needle roller bearings

Request TIMKEN Manufacturer Name A Quote For Your Special NSK FWJ-182417 needle roller bearings Needs Today! Free Quotes. ISO 0.0 Inventory 9001 certified.

|                           |                                      |
|---------------------------|--------------------------------------|
| Inventory                 | 0.0                                  |
| Manufacturer Name         | TIMKEN                               |
| Minimum Buy Quantity      | N/A                                  |
| Weight                    | 57.204                               |
| EAN                       | 0883450308861                        |
| Product Group             | M06288                               |
| Number of Mounting Holes  | 4                                    |
| Mounting Method           | Tapered Adapter Sleeve               |
| Housing Style             | 4 Bolt Pillow Block                  |
| Rolling Element           | Spherical Roller Bearing             |
| Housing Material          | Cast Steel                           |
| Expansion / Non-expansion | Non-expansion                        |
| Mounting Bolts            | 1 Inch                               |
| Relubricatable            | Yes                                  |
| Insert Part Number        | 22226                                |
| Seals                     | Teflon Labyrinth                     |
| Housing Configuration     | 1 Piece Solid                        |
| Inch – Metric             | Metric                               |
| Other Features            | Double Row   Extreme Duty   SN Style |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 115MM Bore; 150MM Base to Center Height; Tapered Adapter Sleeve Mount; Spherica |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Weight / LBS                  | 136  |
| d                             | 4.528 Inch   115 Millimeter  |
| Bolt Spacing Maximum          | 15.75 Inch   400.05Millimeter  |
| B                             | 5.906 Inch   150 Millimeter  |
| D                             | 4.76 Inch   120.904 Millimeter   |
| Nominal Bolt Center to Center | 15.3 Inch   389 Millimeter   |
| Bolt Spacing Minimum          | 14.75 Inch   374.65Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |