

# NSK HJ-648032 + IR-566432 needle roller bearings

Shop NSK HJ-648032 + IR-566432 needle roller bearings huge online discount inventory. and Import machinery parts your car needs 0.0 Inventory with Free Shipping and Free Extended Warranty. TIMKEN Manufacturer Name

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 52.21  |
| EAN                       | 0883450977470  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 6  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 6 Bolt Round Flange Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22226  |
| Seals                     | Triple Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 6 Bolt Round Flange Block; 5" Bore; 14" Bolt Circle; 7" Bolt Spacing; 1 Piece Solid; |

|                                       |  |
|---------------------------------------|--|
| Other Features                        | Double Row   Double Collar  <br>With Set Screw |
| UNSPSC                                | 31171501                                       |
| Harmonized Tariff Code                | 8483.20.40.80                                  |
| Noun                                  | Bearing  |
| Keyword String                        | Flanged  |
| Manufacturer Item Number              | QAAFXP26A500SEM                                |
| Weight / LBS                          | 115  |
| Nominal Bolt Circle Diameter<br>Round | 14 Inch   355.6 Millimeter                     |
| Cartridge Pilot Depth                 | 0.188 Inch   4.775 Millimeter                  |
| Cartridge Pilot Diameter              | 11.188 Inch   284.18 Millimeter                |
| Bolt Spacing                          | 7 Inch   177.8 Millimeter                      |
| d                                     | 5 Inch   127 Millimeter                        |
| D                                     | 7.44 Inch   188.976 Millimeter                 |