

NSK HR130KBE2301+L tapered roller bearings

Offer High Quality Brand 40x52x32 Size (mm) NSK HR130KBE2301+L tapered roller bearings .Contact Us Online to Get 40 Bore Diameter (mm) Best Quote.

Size (mm)	40x52x32
Bore Diameter (mm)	40
Outer Diameter (mm)	52
Width (mm)	32
Fw	40 mm
D	52 mm
C – 32 mm / Tolerance: -0,25	32 mm / Tolerance: 0,25
C1 – 13 mm / Tolerance: -0,2	13 mm / Tolerance: 0,2
C2	10 mm
D1 max	60,1 mm
da	55,7 mm
dw	40 mm / Tolerance: E8
ra max	0,6 mm
rmin	0,6 mm
m	204 g / Weight
Cr	29500 N / Dynamic load rating (radial)
C0r	47000 N / Static load rating (radial)
Ca	56000 N / Dynamic load rating (axial)

C0a	148000 N / Static load rating (axial)
Cur	8300 N / Fatigue limit load, radial
Cua	14500 N / Fatigue limit load, axial
nG	6000 1/min / Limiting speed
nB	2000 1/min / Reference speed
Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.2
EAN	4012802736045
Product Group	B00234
Rolling Element	Combination – Needle Roller and Thrust Roller Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Long Description	40MM Bore 1; 40MM Bore 2; 52MM Outside Diameter; 32MM Height; Combination – Needle Roller and Thrust
Inch – Metric	Metric
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.80

Noun	Bearing
Keyword String	Combination
Manufacturer Item Number	NKXR40
Weight / LBS	0.45
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 1	1.575 Inch 40 Millimeter
Bore 2	1.575 Inch 40 Millimeter
Height	1.26 Inch 32 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter