

# NSK HR30309J tapered roller bearings

Various types and 0.0 Inventory sizes to accommodate your NSK HR30309J tapered roller bearings requirements.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | ASAHI BEARINGS   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 17.978   |
| EAN                       | 0808250334438  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 7/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | UG314-43   |
| Seals                     | Contact Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Spherical   Heavy Duty   Has Slinger  |
| Long Description          | 2 Bolt Pillow Block; 2-11/16" Bore; 4-9/16" Base to Center Height; Eccentric Collar Mount; |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Weight / LBS                  | 36.51                          |
| Nominal Bolt Center to Center | 12 Inch   305 Millimeter       |
| B                             | 4.563 Inch   115.9 Millimeter  |
| Bolt Spacing Maximum          | 12.5 Inch   317.5Millimeter    |
| d                             | 2.688 Inch   68.275 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| D                             | 3.626 Inch   92.1 Millimeter   |
| Bolt Spacing Minimum          | 11.5 Inch   292.1Millimeter    |