

# NSK HR30312DJ tapered roller bearings

Our 0.0 Inventory highly-skilled and factory-trained service experts have the resources to help you with all your NSK HR30312DJ tapered roller bearings needs – including routine maintenance, NTN Manufacturer Name major repairs, warranty service, and equipment inspections.

|                                 |                 |
|---------------------------------|-----------------|
| Inventory                       | 0.0             |
| Manufacturer Name               | NTN             |
| Minimum Buy Quantity            | N/A             |
| Weight                          | 5.566           |
| EAN                             | 4547359309898   |
| Product Group                   | B00152          |
| Enclosure                       | Open            |
| Flush Ground                    | No              |
| Rolling Element                 | Ball Bearing    |
| Number of Rows of Balls         | Double Row      |
| Precision Class                 | ABEC 1   ISO P0 |
| Maximum Capacity / Filling Slot | No              |
| Snap Ring                       | No              |
| Cage Material                   | Steel           |
| Contact Angle                   | 25 Degree       |
| Internal Clearance              | C0-Medium       |
| Number of Bearings              | 1 (Single)      |
| Inch – Metric                   | Metric          |

|                              |   |
|------------------------------|---|
| Long Description             | 75MM Bore; 160MM Outside Diameter; 68.3MM Width; Open; No Flush Ground; Ball Bearing; Double Row of |
| UNSPSC                       | 31171531  |
| Harmonized Tariff Code       | 8482.10.50.28   |
| Noun                         | Bearing   |
| Keyword String               | Angular Contact   |
| Manufacturer Item Number     | 5315  |
| d                            | 2.953 Inch   75 Millimeter  |
| B                            | 2.689 Inch   68.3 Millimeter  |
| D                            | 6.299 Inch   160 Millimeter   |
| bore diameter:               | 75 mm   |
| radial static load capacity: | 145000 N  |
| outside diameter:            | 160 mm  |
| operating temperature range: | -40 to 120 °C   |
| overall width:               | 2.7500 in   |
| cage material:               | Steel   |
| contact angle:               | 25 °  |
| outer ring width:            | 68.3 mm   |
| row type & fill slot:        | Double-Row Non-Fill Slot  |
| maximum rpm:                 | 3200 RPM  |
| internal clearance:          | C0  |
| finish/coating:              | Uncoated  |
| bore type:                   | Round   |
| precision rating:            | Class 0   |
| closure type:                | Open  |
| fillet radius:               | 2.1 mm  |
| snap ring included:          | Without Snap Ring   |
| series:                      | 53  |

|                               |                            |
|-------------------------------|----------------------------|
| bearing material:             | High Carbon Chrome Steel   |
| weight:                       | 5.561 kg                   |
| radial dynamic load capacity: | 173000 N                   |
| manufacturer product page:    | <a href="#">Click here</a> |