NSK HR32208CJ tapered roller bearings

Request A Quote For Your Special NSK HR32208CJ tapered roller bearings Needs Today! Free Quotes. ISO 9001 Mounted Bearing Engineering Group certified.

| Engineering Group | Mounted Bearing |
|-------------------------|-----------------------|
| Shaft Size | 2-1/2 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QAPL13A208SB |
| Locking Style | Single Concentric |
| Weight | 22.00 lb |
| Housing Style | Two-Bolt Pillow Block |
| UPC Code | 0883450047609 |
| Dimension A | 2.75 in |
| Dimension B | 5.8 in |
| Dimension C | 3.81 in |
| Dimension D Max | 7.44 in |
| Dimension D Min | 6.81 in |
| Dimension F | 9.250 in |
| Dimension G | 2.900 in |
| Dimension H | 1.38 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension KA | 1.24 in |
| Dimension L | 3.60 in |
| Dimension M | 2.15 in |
| Dimension RA | 0.21 in |
| Dimension SA | 3.39 in |

| CO — Static Load | 48600 lb |
|-------------------------------------|-----------|
| C — Dynamic Load (Basic) | 46400 lb |
| e — Geometry Factor | 0.24 |
| Y1 - Geometry Factor | 2.79 |
| Y2 - Geometry Factor | 4.15 |
| Oil Lubrication — M/N Seal | 1800 rpm |
| Oil Lubrication — T Seal | 3200 rpm |
| Oil Lubrication — B/C/O Seal | 1500 rpm |
| Grease Lubrication — M/N Seal | 1800 rpm |
| Grease Lubrication — T Seal | 2800 rpm |
| Grease Lubrication — B/C/O Seal | 1500 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance — Min | 0.0016 |
| Eng Internal Radial Clearance — Max | 0.0026 |
| Pre Install Clearance Min | 0.0016 in |
| Pre Install Clearance Max | 0.0026 in |