

NSK HR33007J tapered roller bearings

NSK HR33007J tapered roller bearings manufacturer and global 20x47x20.600 Size (mm) supplier of reliable ball and roller ... NSK HR33007J tapered roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the 47,000 Outer Diameter (mm) unique requirements of our targeted industries.

| | |
|---------------------------------|-----------------|
| Size (mm) | 20x47x20.600 |
| Bore Diameter (mm) | 20,000 |
| Outer Diameter (mm) | 47,000 |
| Width (mm) | 20,600 |
| d | 20,000 mm |
| D | 47,000 mm |
| B | 20,600 mm |
| C | 20,600 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4547359580822 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |

| | |
|------------------------|--|
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 20MM Bore; 47MM Outside Diameter; 20.62MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; |
| Other Features | Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Al |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 0.34 |
| Bore | 0.787 Inch 20 Millimeter |
| Outside Diameter | 1.85 Inch 47 Millimeter |
| Outer Race Width | 0.812 Inch 20.62 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| bore diameter: | 20 mm |
| precision rating: | ISO Class 0 |
| outside diameter: | 47 mm |
| finish/coating: | Uncoated |
| overall width: | 20.6 mm |
| bearing material: | High Carbon Chrome Steel |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Double Sealed |

| | |
|------------------------------|----------------------------|
| inner ring width: | 20.60 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| outer ring width: | 20.60 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm (grease): | 10000 rpm |
| internal clearance: | CN |
| fillet radius: | 1 mm |
| operating temperature range: | -40 to 120 °C |
| series: | 632 |
| dynamic load capacity: | 5100 N |
| manufacturer product page: | Click here |
| static load capacity: | 2390 N |