

# NSK HR33007J tapered roller bearings

NSK HR33007J tapered roller bearings manufacturer and global 20x47x20.600 Size (mm) supplier of reliable ball and roller ... NSK HR33007J tapered roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the 47,000 Outer Diameter (mm) unique requirements of our targeted industries.

Size (mm)	20x47x20.600
Bore Diameter (mm)	20,000
Outer Diameter (mm)	47,000
Width (mm)	20,600
d	20,000 mm
D	47,000 mm
B	20,600 mm
C	20,600 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359580822
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No

Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 20.62MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0;
Other Features	Deep Groove   Cartridge Type   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Al
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.34
Bore	0.787 Inch   20 Millimeter
Outside Diameter	1.85 Inch   47 Millimeter
Outer Race Width	0.812 Inch   20.62 Millimeter
Inner Race Width	0 Inch   0 Millimeter
bore diameter:	20 mm
precision rating:	ISO Class 0
outside diameter:	47 mm
finish/coating:	Uncoated
overall width:	20.6 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed

inner ring width:	20.60 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	20.60 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	10000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 °C
series:	632
dynamic load capacity:	5100 N
manufacturer product page:	<a href="#">Click here</a>
static load capacity:	2390 N