

NSK HR80KBE52X+L tapered roller bearings

How do you 40 mm D find the NSK HR80KBE52X+L tapered roller bearings 17 mm d specification? Manufacturers Online Free check

| | |
|---|------------|
| d | 17 mm |
| D | 40 mm |
| B | 16 mm |
| d1 | 23.9 mm |
| D1 | 33.9 mm |
| rs min | 0.6 mm |
| e | 0.46 |
| Y1 | 1.37 |
| Y2 | 2.12 |
| Y0 | 1.43 |
| Radial clearance class | C3 |
| Precision class | P0 |
| Mass | 0.09 kg |
| Dynamic load, C | 11.5 kN |
| Static load, C0 | 2.75 kN |
| Nref | 18,000 rpm |
| Nlim | 23,000 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.38 Hz |
| Characteristic rolling element frequency, BSF | 3.86 Hz |
| Characteristic outer ring frequency, BPF0 | 3.83 Hz |

| | |
|---|---------|
| Characteristic inner ring frequency, BPFI | 6.17 Hz |
| da min | 21 mm |
| Da max | 36 mm |
| ra max | 0.6 mm |