

# NSK LM603049/LM603011 tapered roller bearings

Browse NSK LM603049/LM603011 tapered roller bearings Categories in the Manufacturers Online Free. including . 12x28x8 Size (mm) 28 Outer Diameter (mm)

Size (mm)	12x28x8
Bore Diameter (mm)	12
Outer Diameter (mm)	28
Width (mm)	8
d	12 mm
D	28 mm
B	8 mm
C	8 mm
r min.	0,3 mm
da min.	14 mm
da max	16 mm
Da max.	26 mm
ra max.	0,3 mm
Weight	0,021 Kg
Basic dynamic load rating (C)	5,1 kN
Basic static load rating (C0)	2,39 kN
(Grease) Lubrication Speed	26 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.02
EAN	4547359003574

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	12MM Bore; 28MM Outside Diameter; 8MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6001LLB/2AS
Weight / LBS	0.045
Outer Race Width	0.315 Inch   8 Millimeter
Outside Diameter	1.102 Inch   28 Millimeter
Bore	0.472 Inch   12 Millimeter
bore diameter:	12 mm
static load capacity:	2390 N
outside diameter:	28 mm
precision rating:	ISO Class 0
overall width:	8 mm
finish/coating:	Uncoated

bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	8 mm
snap ring included:	Without Snap Ring
outer ring width:	8 mm
internal clearance:	CN
maximum rpm (grease):	26000 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	0.3 mm
dynamic load capacity:	5100 N
manufacturer product page:	<a href="#">Click here</a>