

NSK M-1671 needle roller bearings

High Quality NSK M-1671 needle roller bearings. 45x100x25 Size (mm) 45 Bore Diameter (mm) Competitive Pricing. Accept Small Order. Easy and Fast Shipping.

Size (mm)	45x100x25
Bore Diameter (mm)	45
Outer Diameter (mm)	100
Width (mm)	25
d	45 mm
Fw	58,5 mm
D	100 mm
B	25 mm
C	25 mm
r min.	1,5 mm
r1 min.	1,5 mm
Weight	0,91 Kg
Basic dynamic load rating (C)	97,5 kN
Basic static load rating (C0)	98,5 kN
(Grease) Lubrication Speed	6000 r/min
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	45 mm
Outside Diameter	100 mm
Width	25 mm
Fillet Radius/Chamfer	1.5 mm

r1	1.5 mm
Dynamic Load Rating	97,500 N
Static Load Rating	98,500 N
Limiting Speed – Grease	6,000 rpm
Limiting Speed – Oil	7,500 rpm
Radial Clearance	0.030 to 0.060 mm
db (min)	53.5 mm
db (max)	57 mm
dc (min)	60 mm
dd (min)	66 mm
Da (max)	91.5 mm
ra (max)	1.5 mm
ra1 (max)	1.5 mm