

# NSK MF-58 needle roller bearings

Can't find what you're looking 61,913 Bore Diameter (mm) for NSK MF-58 needle roller bearings ? Our 61,913 mm d expert Representatives be in contact with you shortly!

Bore Diameter (mm)	61,913
Width (mm)	65,1
d	61,913 mm
s1	39.7 mm
A1	17 mm
B	65,1 mm
G	16 mm
J	143 mm
L	175 mm
T	73,7 mm
A2	17 mm
Weight	4,6 Kg
Basic dynamic load rating (C)	52,7 kN
Basic static load rating (C0)	36 kN
Fatigue load limit (Pu)	1,53
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.976
EAN	7316577758392
Product Group	M06110
Number of Mounting Holes	4

Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 212-207-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 2-7/16" Bore; 7.9" Bolt Circle; 5-5/8" Bolt Spacing; 1 Pi
Other Features	Single Row   Standard Duty   Wide Inner Race   Open End   Has Flinger   Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 2.7/16 TF
Weight / LBS	9.4
Bolt Spacing	5.625 Inch   142.88 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Bore	2.438 Inch   61.925 Millimeter

Length Thru Bore	2.563 Inch   65.09 Millimeter
Nominal Bolt Circle Diameter Round	7.9 Inch   200 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Housing material	Cast iron
Da	161.9 mm
Db1	130 mm
Db2	143 mm
A	52 mm
A3	3.2 mm
A5	39 mm
N	18 mm
RG	1/4-28 UNF
R1	34.5 mm
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	161 mm
J7	49.5 mm
N4	4 mm
Basic dynamic load rating C	52.7 kN
Basic static load rating C0	36 kN
Fatigue load limit Pu	1.53 kN
Limiting speed	3400 r/min
Mass bearing unit	3.85 kg
Thread grub screw G2	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm

Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Housing	FY 512 M
Bearing	YAR 212-207-2F
End cover	ECY 212