

# NSK N1013RXZTPKR cylindrical roller bearings

Offer High Quality Brand NSK N1013RXZTPKR cylindrical roller bearings 15x35x13.8 Size (mm) .Contact Us 15 Bore Diameter (mm) Online to Get Best Quote.

Size (mm)	15x35x13.8
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Width (mm)	13,8
D	35 mm
d	15 mm
C	13.8 mm
B	14 mm
D1	26 mm
F	20 mm
r1,2 – min.	0.6 mm
r3,4 – min.	0.3 mm
Basic dynamic load rating – C	7.5 kN
Basic static load rating – C0	9.3 kN
Fatigue load limit – Pu	1.1 kN
Maximum dynamic radial loads – Fr	9.5 kN
Maximum static radial loads – F0r	13.7 kN
Limiting speed	5000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.081

EAN	7316577011930
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Yoke Type
Enclosure	Sealed
Rolling Element	Needle Bearing
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Caged   With Inner Ring   Lip Seal
Long Description	15MM Bore; 35MM Roller Diameter; 13.8MM Roller Width; Crowned Roller; Yoke Type; Sealed; Needle Bear
UNSPSC	31171530
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	NA 2202.2RS
Weight / LBS	0.165
Roller Diameter	1.378 Inch   35 Millimeter
Roller Width	0.543 Inch   13.8 Millimeter
Bore	0.591 Inch   15 Millimeter
roller diameter:	35 mm
radial static load capacity:	13.7 kN
roller width:	13.8 mm
roller material:	Chrome Steel

bore diameter:	15 mm
maximum rpm:	5000 RPM
roller shape:	Crowned
lubrication hole location:	Inner Ring
bearing element:	Needle Rollers
axial dynamic load capacity:	7.21 kN
closure type:	Sealed
axial static load capacity:	9 kN
operating temperature range:	Maximum of +280 °F
finish/coating:	Uncoated
radial dynamic load capacity:	9.65 kN
standards met:	ANSI/ABMA Standard 18.1
r1,2 min.	0.6 mm
r3,4 min.	0.3 mm
Basic dynamic load rating C	7.48 kN
Basic static load rating C0	9.3 kN
Fatigue load limit Pu	1.12 kN
Maximum dynamic radial load Fr max.	9.5 kN
Maximum static radial load F0r max.	13.7 kN
Mass support roller	0.075 kg