

NSK NA69/22TT needle roller bearings

NSK NA69/22TT needle roller bearings Needs Analysis , Manufacturing 28 Outer Diameter (mm) Service . 25x28x20 Size (mm) Get 25 Bore Diameter (mm) Your Free.

Size (mm)	25x28x20
Bore Diameter (mm)	25
Outer Diameter (mm)	28
Width (mm)	20
d	25 mm
D	28 mm
B	20 mm
c1 min	0,1 mm
c2 min	0,2 mm
M	– mm
Weight	0,018 Kg
Basic dynamic load rating (C)	38 kN
c1 min.	0.1 mm
c1 max.	0.7 mm
c2 min.	0.2 mm
c2 max.	1 mm
$\alpha \pm 8$	20 °
Tolerance shaft	f7
Tolerance housing	H7
Basic dynamic load rating – radial direction C	38 kN
Basic static load rating – radial direction C0	120 kN
Specific dynamic load factor K	80 N/mm ²

Specific static load factor K_0	250 N/mm ²
Factor depending on material and bearing type K_M	480
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2 m/s
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Mass bushing	0.018 kg