

NSK NN3944MBKR cylindrical roller bearings

How do you find the NSK NN3944MBKR cylindrical roller bearings 52x20x22.25 Size (mm) specification? Manufacturers Online Free 20 Outer Diameter (mm) check

Size (mm)	52x20x22.25
Bore Diameter (mm)	52
Outer Diameter (mm)	20
Width (mm)	22,25
d	20 mm
D	52 mm
T	22.25 mm
d1	34.6 mm
B	21 mm
C	18 mm
r1,2 – min.	1.5 mm
r3,4 – min.	1.5 mm
a	14 mm
da – max.	27 mm
db – min.	27.5 mm
Da – min.	43 mm
Da – max.	45.5 mm
Db – min.	47 mm
Ca – min.	3 mm
Cb – min.	4 mm
ra – max.	1.5 mm
rb – max.	1.5 mm

Basic dynamic load rating – C	44 kN
Basic static load rating – C0	45.5 kN
Fatigue load limit – Pu	5 kN
Reference speed	10000 r/min
Limiting speed	14000 r/min
Calculation factor – e	0.3
Calculation factor – Y	2
Calculation factor – Y0	1.1
Inventory	11.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.242
EAN	7316570777611
Product Group	B04334
bore diameter:	20 mm
operating temperature range:	Maximum of +250 °F
cup width:	18 mm
dynamic load capacity:	44 kN
assembly type:	Cone & Cup
static load capacity:	45.5 kN
outside diameter:	52 mm
finish/coating:	Uncoated
cone width:	21 mm
maximum rpm:	14000 RPM
closure type:	Open
series:	323
cage material:	Steel
flange type:	Non-Flanged Cup