

NSK NNCF4926V cylindrical roller bearings

NSK NNCF4926V cylindrical roller bearings SEARCH 130 Bore Diameter (mm) 230 Outer Diameter (mm) – Whether it's agriculture or construction equipment your working 130x230x40 Size (mm) on, Has the you need.

Size (mm)	130x230x40
Bore Diameter (mm)	130
Outer Diameter (mm)	230
Width (mm)	40
d	130 mm
D	230 mm
B	40 mm
C	40 mm
Angle (α)	30 °
a	32 mm
r min.	3 mm
r1 min.	1.1 mm
2B	80 mm
da min.	137 mm
Da max.	223 mm
ra max.	1 mm
Weight	6.88 Kg
Basic dynamic load rating (C)	320 kN
Basic static load rating (C0)	395 kN
(Grease) Lubrication Speed	1900 r/min
Bore Type	Cylindrical Bore

Enclosure	Open
Configuration	Duplex
Bore Size	130 mm
Outside Diameter	230 mm
Width	40 mm
Fillet Radius/Chamfer	3 mm
r1	1.1 mm
Dynamic Load Rating	320,000 N
Static Load Rating	395,000 N
Limiting Speed – Grease	1,900 rpm
Limiting Speed – Oil	2,500 rpm
da1 (min)	144 mm
da2 (min)	137 mm
Da1 (max)	216 mm
Da2 (max)	223 mm
ra (max)	2.5 mm
ra1 (max)	1 mm