

# NSK NNCF4934V cylindrical roller bearings

How do 266.7 mm da 419.999 mm Da you find the NSK NNCF4934V cylindrical roller bearings specification? Manufacturers 147.803 mm Ca Online Free check

da	266.7 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	315.119 mm
ba	100.806 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J1	139.7 mm
L	869.95 mm
N1	41.275 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	73.025 mm
Housing	SAFS 056 KAUA
Bearing	23056 CCK/W33
Adapter sleeve assembly	SNP 3056×10.1/2

Stabilizing ring	2 x A8819
Labyrinth ring	2 x LOR 519
PosiTrac Plus contact element	2 x B10724-606
End plug (suffix Y)	X-5217-2
Max. speed for PosiTrac Plus seal	575 r/min
P60°	669 kN
P90°	400 kN
P120°	249 kN
P150°	222 kN
P180°	267 kN
Pa	89 kN
Mass pillow block	298 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g